

# TERRORIST SPOIL & EQUIPMENT WASTE 1

## PUBLIC AWARENESS CHART 13

Supplementary technical data and photographs relative to this chart available on request.

Copyright © 1987 by Patrick Gencke. All rights reserved internationally. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical or chemical, including photocopying, filming, recording or by any information storage and retrieval system without written permission from the publisher. Inquiries should be addressed to the publishing address shown in this publication. Any infringement will result in litigation.



This poster is the copyright of the promoters. Any infringement will result in litigation.

**MD2M detonators**

**Fuse spanner**

**Full range of variable delay lead staffs.**

**VZD-IM fuse, containers and accessories.**

**Assortment of fuse containers with fuse and detonator**

**VZD-3M fuse and container.**

**Canvas carrying strap is sometimes cut off prior to laying to prevent easy removal of limpet mine from target.**

**Single page leaflet instruction detailing temperature time delays.**

**TYPE 158 LIMPET**

**VZD-IM Fuse mechanism being tightened into position.**

**Canvas carrying strap**

**Body**

**Fuse**

**Shipping/keeper plate removed from limpet immediately prior to attachment to target.**

**Limpet mine as it is frequently carried by belt around layers waist. Belt may be used to attach limpet to non metallic targets.**

**Detonator well dust cap. Removed immediately prior to insertion of fuse.**

**Arming pin pulled out to arm mine, procedure normally executed after mine has been attached to target.**

**SPM LIMPET**

**LIMPET MINES**

**SZ-6 Detonator well transit plug, booster well cap and screwdriver**

**Grenade firing mechanisms Grenade firing mechanisms (one with detonator) are transported separately from grenade body in containers below.**

**Tin Opener**

**Dust caps from FI, RG-42 and RGD-5 grenades (Interchangeable)**

**Dust cap from stick grenade**

**HAND GRENADES**

**TERRORIST SPOIL AND EQUIPMENT WASTE**

All terrorist mines, bombs or devices need preparation and arming before they can be laid effectively. During the preparation, arming and laying of these devices, spoil and equipment waste in the form of plugs, containers, batteries, loose wire, arming pins, base-plates, and severed carry-straps need to be disposed of. Having laid the explosive device, the terrorists will not want to be caught with any of this evidence, and will quickly dispose of it, often not burying it; more often than not he will toss the waste to one side of the road or path, in the area in which he is working.

The presence of these indicators or telltale signs are early warning signals that will alert you to the presence of the device or the layer thus enabling you to take the necessary precautions against the threat and give timely warnings to police. Items shown on this page are from terrorist devices illustrated in our matching poster series numbers 1-6, and represent the more common spoil and waste material found.

**WARNING: If any spoil or waste as shown is seen it must not be touched, but must be reported immediately to the nearest police station or any military unit.**